



SCOPE OF ACCREDITATION

Laboratory Name:

SCHOOL OF ELECTRICAL ENGINEERING CALIBRATION LABORATORY, VELLORE INSTITUTE OF TECHNOLOGY, VELLORE CAMPUS TECHNOLOGY TOWER BUILDING, FOURTH FLOOR, ROOM NO. 401, KATPADI, THIRUVALAM ROAD,

VELLORE, TAMIL NADU, INDIA

Accreditation Standard

ISO/IEC 17025:2017

Certificate Number

CC-4371 Page No

1 of 6

Validity

17/04/2025 to 04/12/2028

S.No	Discipline / Group	Measurand or Reference Material/Type of instrument or material to be calibrated or measured / Quantity Measured /Instrument	Calibration or Measurement Method or procedure	Measurement range and additional parameters where applicable(Range and Frequency)	* Calibration and Measurement Capability(CMC)(±)
		1 30	Permanent Facility		
1	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Measure)	AC Current @ 45 Hz & 1 kHz	Using 6½ Digital Multimeter by direct method	329 μA to 329 mA	0.95 % to 0.65 %
2	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Measure)	AC Current @ 45 Hz & 1 kHz	Using 6½ Digital Multimeter by direct method	30 μA to 329 μA	3 % to 0.95 %
3	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Measure)	AC Current @ 45 Hz & 1 kHz	Using 6½ Digital Multimeter by direct method	329 mA to 10 A	0.65 % to 0.1 %
4	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Measure)	AC Voltage @ 45 Hz & 1 kHz	Using 6½ Digital Multimeter by direct method	1 mV to 300 mV	2.69 % to 2.60 %





SCOPE OF ACCREDITATION

Laboratory Name:

SCHOOL OF ELECTRICAL ENGINEERING CALIBRATION LABORATORY, VELLORE INSTITUTE OF TECHNOLOGY, VELLORE CAMPUS TECHNOLOGY TOWER BUILDING, FOURTH FLOOR, ROOM NO. 401, KATPADI, THIRUVALAM ROAD,

VELLORE, TAMIL NADU, INDIA

Accreditation Standard

ISO/IEC 17025:2017

Certificate Number

CC-4371

Page No

2 of 6

Validity

17/04/2025 to 04/12/2028

S.No	Discipline / Group	Measurand or Reference Material/Type of instrument or material to be calibrated or measured / Quantity Measured /Instrument	Calibration or Measurement Method or procedure	Measurement range and additional parameters where applicable(Range and Frequency)	* Calibration and Measurement Capability(CMC)(±)
5	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Measure)	AC Voltage @ 45 Hz & 1 kHz	Using 6½ Digital Multimeter by direct method	300 mV to 1000 V	2.60 % to 0.07 %
6	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Source)	AC Current @ 45 Hz & 1 kHz	Using Multiproduct calibrator by direct method	30 μA to 329 μA	3 % to 0.95 %
7	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Source)	AC Current @ 45 Hz & 1 kHz	Using Multiproduct calibrator by direct method	329 μA to 329 mA	0.95 % to 0.65 %
8	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Source)	AC Current @ 45 Hz & 1kHz	Using Multiproduct calibrator by direct method	329 mA to 20 A	0.65 % to 0.21 %
9	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Source)	AC Voltage @ 45 Hz & 1 kHz	Using Multiproduct calibrator by direct method	1 mV to 300 mV	6.28 % to 6.96 %





SCOPE OF ACCREDITATION

Laboratory Name:

SCHOOL OF ELECTRICAL ENGINEERING CALIBRATION LABORATORY, VELLORE INSTITUTE OF TECHNOLOGY, VELLORE CAMPUS TECHNOLOGY TOWER BUILDING, FOURTH FLOOR, ROOM NO. 401, KATPADI, THIRUVALAM ROAD,

VELLORE, TAMIL NADU, INDIA

Accreditation Standard

ISO/IEC 17025:2017

Certificate Number

CC-4371

Page No

3 of 6

Validity

17/04/2025 to 04/12/2028

S.No	Discipline / Group	Measurand or Reference Material/Type of instrument or material to be calibrated or measured / Quantity Measured /Instrument	Calibration or Measurement Method or procedure	Measurement range and additional parameters where applicable(Range and Frequency)	* Calibration and Measurement Capability(CMC)(±)
10	ELECTRO- TECHNICAL- Alternating Current (< 1 GHz) (Source)	AC Voltage @ 45 Hz & 1 kHz	Using Multiproduct calibrator by direct method	300 mV to 1000 V	6.96 % to 0.08 %
11	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	DC Current	Using 6½ Digital Multimeter by direct method	1 mA to 329 mA	0.35 % to 0.14 %
12	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	DC Current	Using 6½ Digital Multimeter by direct method	1.09 A to 10 A	0.07 % to 0.002 %
13	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	DC Current	Using 6½ Digital Multimeter by direct method	10 μA to 329 μA	2.4 % to 0.45 %
14	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	DC Voltage	Using 6½ Digital Multimeter by direct method	1 V to 1000 V	0.39 % to 0.008 %
15	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	DC Voltage	Using 6½ Digital Multimeter by direct method	100 mV to 329 mV	0.01 % to 0.02 %





SCOPE OF ACCREDITATION

Laboratory Name:

SCHOOL OF ELECTRICAL ENGINEERING CALIBRATION LABORATORY, VELLORE INSTITUTE OF TECHNOLOGY, VELLORE CAMPUS TECHNOLOGY TOWER BUILDING, FOURTH FLOOR, ROOM NO. 401, KATPADI, THIRUVALAM ROAD,

VELLORE, TAMIL NADU, INDIA

Accreditation Standard

ISO/IEC 17025:2017

Certificate Number

CC-4371

Page No

4 of 6

Validity

17/04/2025 to 04/12/2028

S.No	Discipline / Group	Measurand or Reference Material/Type of instrument or material to be calibrated or measured / Quantity Measured /Instrument	Calibration or Measurement Method or procedure	Measurement range and additional parameters where applicable(Range and Frequency)	* Calibration and Measurement Capability(CMC)(±)
16	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	Resistance - 4 wire	Using 6½ Digital Multimeter by direct method	10 ohm to 300 ohm	0.01 %
17	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	Resistance - 4 wire	Using 6½ Digital Multimeter by direct method	300 kohm to 1000 Mohm	0.015 % to 2.27 %
18	ELECTRO- TECHNICAL- DIRECT CURRENT (Measure)	Resistance - 4 wire	Using 6½ Digital Multimeter by direct method	300 ohm to 300 kohm	0.01 % to 0.015 %
19	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	DC Current	Multiproduct calibrator by direct method	1 mA to 329 mA	0.35 % to 1.90 %
20	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	DC Current	Multiproduct calibrator by direct method	1.09 A to 20 A	0.05 % to 0.12 %
21	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	DC Current	Multiproduct calibrator by direct method	10 μA to 329 μA	2.4 % to 1.92 %





SCOPE OF ACCREDITATION

Laboratory Name:

SCHOOL OF ELECTRICAL ENGINEERING CALIBRATION LABORATORY, VELLORE INSTITUTE OF TECHNOLOGY, VELLORE CAMPUS TECHNOLOGY TOWER BUILDING, FOURTH FLOOR, ROOM NO. 401, KATPADI, THIRUVALAM ROAD,

VELLORE, TAMIL NADU, INDIA

Accreditation Standard

ISO/IEC 17025:2017

Certificate Number

CC-4371

Page No

5 of 6

Validity

17/04/2025 to 04/12/2028

S.No	Discipline / Group	Measurand or Reference Material/Type of instrument or material to be calibrated or measured / Quantity Measured /Instrument	Calibration or Measurement Method or procedure	Measurement range and additional parameters where applicable(Range and Frequency)	* Calibration and Measurement Capability(CMC)(±)
22	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	DC Voltage	Using Multiproduct calibrator by direct method	1 mV to 329 mV	5.78 % to 0.18 %
23	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	DC Voltage	Using Multiproduct calibrator by direct method	1 V to 1000 V	0.06 % to 0.06 %
24	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	Resistance - 4 wire	Using Multiproduct calibrator by direct method	1 ohm to 300 ohm	5.25 % to 0.19 %
25	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	Resistance - 4 wire	Multiproduct calibrator by direct method	300 kohm to 1090 Mohm	0.02 % to 1.72 %
26	ELECTRO- TECHNICAL- DIRECT CURRENT (Source)	Resistance - 4 wire	Using Multiproduct calibrator by direct method	300 ohm to 300 kohm	0.19 % to 0.02 %
27	ELECTRO- TECHNICAL- TIME & FREQUENCY (Measure)	Frequency @ 3 V	Using 6½ Digital Multimeter by direct method	1 kHz to 100 kHz	0.73 % to 0.33 %





SCOPE OF ACCREDITATION

Laboratory Name:

SCHOOL OF ELECTRICAL ENGINEERING CALIBRATION LABORATORY, VELLORE INSTITUTE OF TECHNOLOGY, VELLORE CAMPUS TECHNOLOGY TOWER BUILDING, FOURTH FLOOR, ROOM NO. 401, KATPADI, THIRUVALAM ROAD,

VELLORE, TAMIL NADU, INDIA

Accreditation Standard

ISO/IEC 17025:2017

Certificate Number

CC-4371

Page No

6 of 6

Validity

17/04/2025 to 04/12/2028

S.No	Discipline / Group	Measurand or Reference Material/Type of instrument or material to be calibrated or measured / Quantity Measured /Instrument	Calibration or Measurement Method or procedure	Measurement range and additional parameters where applicable(Range and Frequency)	* Calibration and Measurement Capability(CMC)(±)
28	ELECTRO- TECHNICAL- TIME & FREQUENCY (Measure)	Frequency @ 3 V	Using 6½ Digital Multimeter by direct method	10 Hz to 120 Hz	0.06 % to 0.73 %
29	ELECTRO- TECHNICAL- TIME & FREQUENCY (Source)	Frequency @ 3 V	Multiproduct calibrator by direct method	1 Hz to 120 Hz	3.1 % to 0.73 %
30	ELECTRO- TECHNICAL- TIME & FREQUENCY (Source)	Frequency @ 3 V	Multiproduct calibrator by direct method	120 Hz to 100 kHz	0.73 % to 0.33 %
31	THERMAL- TEMPERATURE	RTD / Thermocouple with or without indicator / Recorder / Controller, Digital Thermometer, Temperature Gauge, Switch, Transducer Transmitter with sensor	Using Precision RTD Temperature Probe with Indicator, 6½ Digital Multimeter, Dry block calibrator by Comparison method	(-)25 °C to 150 °C	0.28 °C

^{*} CMCs represent expanded uncertainties expressed at approximately the 95% level of confidence, using a coverage factor of k = 2.